

LMK 331

Screw-In Transmitter

Ceramic Sensor

accuracy according to IEC 60770:
0.5 % FSO



Nominal pressure

from 0 ... 400 mbar up to 0 ... 60 bar

Output signals

2-wire: 4 ... 20 mA

3-wire: 0 ... 20 mA / 0 ... 10 V

others on request

Special characteristics

- ▶ pressure port G 3/4" flush for pasty and impurified media
- ▶ pressure port PVDF for aggressive media





Optional versions

- ▶ IS-version (only for 4 ... 20mA / 2-wire):
Ex ia = intrinsically safe for gases and dusts
- ▶ SIL 2 application according to IEC 61508 / IEC 61511
- ▶ customer specific versions

The screw-in transmitter LMK 331 has been especially designed for level and process measurement and is suitable for pressure measurement of liquids, oils and gases. Usage in more viscous or polluted media is possible because of the semi-flush pressure sensor.

For the usage in aggressive media we recommended the version with PVDF pressure port. Additional features like e.g. an intrinsically safe version or a functionally safe version (SIL 2) complete the range of possibilities.

Preferred areas of use are

-  Plant and Machine Engineering
-  Energy Industry
-  Environmental Engineering (water – sewage – recycling)
-  Medical Technology



Input pressure range													
Nominal pressure gauge	[bar]	0.4	0.6	1	1.6	2.5	4	6	10	16	25	40 ¹	60 ¹
Level	[mH ₂ O]	4	6	10	16	25	40	60	100	160	250	400	600
Overpressure	[bar]	1	2	2	4	4	10	20	20	40	100	100	200
Burst pressure	[bar]	2	4	4	5	5	12	25	25	50	120	120	250
Vacuum resistance	[bar]	P _N ≥ 1 bar: unlimited vacuum resistance P _N < 1 bar: on request											

¹ only possible with stainless steel pressure port

Output signal / Supply	
Standard	2-wire: 4 ... 20 mA / V _S = 8 ... 32 V _{DC}
Option IS-protection ²	2-wire: 4 ... 20 mA / V _S = 10 ... 28 V _{DC}
Optionen 3-wire	3-wire: 0 ... 20 mA / V _S = 14 ... 30 V _{DC} 0 ... 10 V / V _S = 14 ... 30 V _{DC}

² IS-protection not possible with plastic pressure port

Performance	
Accuracy ³	≤ ± 0.5 % FSO
Permissible load	current 2-wire: R _{max} = [(V _S - V _{S min}) / 0.02 A] Ω current 3-wire: R _{max} = 500 Ω voltage 3-wire: R _{min} = 10 kΩ
Influence effects	supply: 0.05 % FSO / 10 V load: 0.05 % FSO / kΩ
Response time	2-wire: ≤ 10 msec 3-wire: ≤ 3 msec

³ accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability)

Thermal effects (Offset and Span) / Permissible Temperatures	
Thermal error	≤ ± 0.2 % FSO / 10 K
in compensated range	-25 ... 85 °C
Permissible temperatures	medium: -40 ... 125 °C electronics / environment: -40 ... 85 °C storage: -40 ... 100 °C

Electrical protection	
Short-circuit protection	permanent
Reverse polarity protection	no damage, but also no function
Electromagnetic compatibility	emission and immunity according to EN 61326

Mechanical stability	
Vibration	10 g RMS (25 ... 2000 Hz) according to DIN EN 60068-2-6
Shock	500 g / 1 msec according to DIN EN 60068-2-27


Materials			
Pressure port / housing	standard:	pressure port	housing
	options for P _N ≤ 25 bar:	stainless steel 1.4404 (316L) PVDF	stainless steel 1.4404 (316L) PVDF
Option compact field housing	stainless steel 1.4305 with cable gland brass nickel plated others on request		
Seals	standard: FKM options: EPDM, NBR, others on request		
Diaphragm	ceramics Al ₂ O ₃ 96 %		
Media wetted parts	pressure port, seals, diaphragm		

Explosion protection (only for 4 ... 20 mA / 2-wire)	
Approval DX19-LMK 331 only for stainless steel pressure port	IBExU 10 ATEX 1068 X / IECEx IBE 12.0027X zone 0: II 1G Ex ia IIC T4 Ga zone 20: II 1D Ex ia IIIC T 85°C Da
Safety technical maximum values	U _i = 28 V, I _i = 93 mA, P _i = 660 mW, C _i ≈ 0 nF, L _i ≈ 0 μH, the supply connections have an inner capacity of max. 27 nF to the housing
Permissible temperatures for environment	in Zone 0: -20 ... 60 °C with p _{atm} 0.8 bar up to 1.1 bar in Zone 1 or higher: -25 ... 70 °C
Connecting cables (by factory)	cable capacitance: signal line/shield also signal line / signal line: 160 pF/m cable inductance: signal line /shield also signal line / signal line: 1 μH/m


Miscellaneous	
Option SIL 2 application	according to IEC 61508 / IEC 61511
Current consumption	signal output current: max. 25 mA signal output voltage: max. 7 mA
Weight	approx. 150 g
Installation position	any
Operational life	> 100 x 10 ⁶ pressure cycles
CE-conformity	EMC Directive: 2004/108/EC
ATEX Directive	94/4/EG

Wiring diagrams

2-wire-system (current)



3-wire-system (current / voltage)




Pin configuration

Electrical connections	ISO 4400	Binder 723 (5-pin)	M12x1 / metal (4-pin)	cable colours (DIN 47100)
Supply +	1	3	1	wh (white)
Supply -	2	4	2	bn (brown)
Signal + (only for 3-wire)	3	1	3	gn (green)
Shield	ground contact	5	4	gn/ye (green / yellow)

Electrical connections (dimensions in mm)

standard

option



⇒ universal stainless steel housing 1.4404 with cable gland M20x1.5 (ordering code 880) and other versions on request


⁴ standard: 2 m PVC-cable without ventilation tube (permissible temperature: -5 ... 70°C)

⁵ different cable types and length available, permissible temperature depends on kind of cable

Mechanical connection (dimensions in mm)

standard

standard for SIL- and SIL-Ex-version



This data sheet contains product specification, properties are not guaranteed. Subject to change without notice.

Ordering code LMK 331

LMK 331



Pressure		4	6	0													
gauge in bar		4	6	0													
gauge in mH ₂ O		4	6	1													
Input		[mH ₂ O]	[bar]														
	4.0	0.40		4	0	0	0										
	6.0	0.60		6	0	0	0										
	10	1.0		1	0	0	1										
	16	1.6		1	6	0	1										
	25	2.5		2	5	0	1										
	40	4.0		4	0	0	1										
	60	6.0		6	0	0	1										
	100	10		1	0	0	2										
	160	16		1	6	0	2										
	250	25		2	5	0	2										
	400	40 ¹		4	0	0	2										
	600	60 ¹		6	0	0	2										
	customer			9	9	9	9										consult
Analogue output																	
	4 ... 20 mA / 2-wire						1										
	0 ... 20 mA / 3-wire						2										
	0 ... 10 V / 3-wire						3										
	Intrinsic safety 4 ... 20 mA / 2-wire ²						E										
	SIL2 4 ... 20 mA / 2-wire						1S										
	SIL2 with Intrinsic safety ²						ES										
	4 ... 20 mA / 2-wire						9										consult
	customer						9										
Accuracy																	
	0.5 %						5										
	customer						9										consult
Electrical connection																	
	Male and female plug ISO 4400						1	0	0								
	Male plug Binder series 723 (5-pin)						2	0	0								
	Cable outlet with PVC cable ³						T	A	0								
	Cable outlet with cable						T	R	0								
	Male plug M12x1 (4-pin) / metal						M	1	0								
	compact field housing						8	5	0								
	stainless steel 1.4305						9	9	9								consult
	customer						9	9	9								
Mechanical connection																	
	G3/4" DIN 3852 with								K	0	0						
	flush sensor								9	9	9						consult
	customer								9	9	9						
Seals																	
	FKM																1
	NBR																5
	EPDM																3
	customer																9
																	consult
Pressure port																	
	Stainless steel 1.4404 (316L)																1
	for P _N £ 25 bar																B
	PVDF ²																9
	customer																consult
Diaphragm																	
	Ceramics Al ₂ O ₃ 96%																2
	customer																9
																	consult
Special version																	
	standard																0 0 0
	customer																9 9 9
																	consult

¹ only possible for pressure port of stainless steel
² Ex-protection not possible with plastic pressure port
³ standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C)