


# coaxial valve

## type **KB 20**



**2/2 way valve** direct acting  
**pressure range** PN 0-50 bar  
**orifice** DN 8-14 mm  
**connection** thread  
**function** valve normally closed  
**symbol** **NC**



**⚠** Above stated body materials refer to the valve port connections that get in contact with the media only!

**design** pressure balanced, with spring return  
**body materials** ⑧ 1.4104/steel, nickel plated ②  
 ③ ⑤  
 ④ ⑥ stainless steel, steel, nickel plated  
**valve seat** synthetic resin on metal  
**seal materials** NBR, PTFE **FPM**

**details needed**

- orifice
- port
- function NC
- operating pressure
- flow rate
- media
- media temperature
- ambient temperature
- nominal voltage

**general specifications**

**options**

<b>ports</b>	KB	threads G 1/2	special thread NPT 1/2
<b>function</b>	NC		
<b>pressure range</b>	bar	50   35   25   15	
	DN	8   10   12   14	
<b>Kv value</b>	m <sup>3</sup> /h	1,8   2,5   2,9   3,2	
<b>vacuum</b>	leak rate		< 10 <sup>-6</sup> mbar•l•s <sup>-1</sup>
<b>pressure-vacuum</b>	P <sub>1</sub> ⇄ P <sub>2</sub>		
<b>back pressure</b>	P <sub>2</sub> > P <sub>1</sub>		
<b>media</b>	gaseous - liquid		
<b>abrasive media</b>			
<b>damping</b>	opening		
	closing		
<b>flow direction</b>	A ⇄ B	as marked	
<b>switching cycles</b>	1/min	150	
<b>switching time</b>	ms	opening 120	closing 270
<b>media temperature</b>	°C	DC: -20 to +100	<-40 °C / -196 °C and >100 °C upon request
		AC: -20 to +100	<-40 °C / -196 °C and >100 °C upon request
<b>ambient temperature</b>	°C	DC: -20 to +80	
		AC: -20 to +80	
<b>limit switches</b>			
<b>manual override</b>			
<b>approvals</b>	WAZ		
<b>mounting</b>			
<b>weight</b>	kg	3,5	
<b>additional equipment</b>			

**electrical specifications**

**options**

<b>nominal voltage</b>	U <sub>n</sub>	DC 24 V	special voltage upon request
	U <sub>n</sub>	AC 230 V 40-60 Hz	special voltage upon request
<b>actuation</b>	DC	direct-current magnet	
	AC	direct-current magnet with integrated rectifier	above 100 °C with separate rectifier
<b>insulating rating</b>	H	180°C	
<b>protection</b>	IP65		
<b>energized duty rating</b>	ED	100%	
<b>connection</b>		plug acc. DIN EN 175301-803 form A, 4 positions x90° / wire diameter 6-8 mm	terminal box M16x1,5
<b>optional additional equipment</b>	M12x1	connector acc. DESINA	connector acc. VDMA
<b>current consumption</b>		illuminated plug with varistor	
		DC 24 V 2,64 A	
		AC 230 V 40-60 Hz 0,30 A	
<b>explosion proof</b>			
<b>limit switches</b>			

**⚠** The valves' technical design is based on media and application requirements. This can lead to deviations from the general specifications shown on the data sheet with regards to the design, sealing materials and characteristics.

**⚠** If order or application specifications are incomplete or imprecise there exists a risk of an incorrect technical design of the valve for the required application. As a consequence, the physical and / or chemical properties of the materials or seals used, may not be suitable for the intended application.

■ specifications not highlighted are standard  
 ■ specifications highlighted in grey are optional

# Type **KB 20**

function: **NC**  
closed when not energized

