



PRO

XPB-P11 AND XPB-P35



PARALLEL PLATFORM TECHNOLOGY

The ability of the power box to be combined with different energy sources and to sum up their combined power outputs.

UNIQUE BI-DIRECTIONAL HYBRID INVERTER

In-house designed interface technology allowing the Power Box to charge and discharge using only one inverter.

UNIQUE ACTIVE BATTERY MANAGEMENT SYSTEM (ABMS)

Monitoring and controls to actively ensure maximum battery life span and optimum efficiency are achieved.

PLUG & PLAY

Easy installation and with the possibility to combine the Power Box with grid supply, renewable energy sources and a generator.

BACKUP POWER

Blackout? With the Power Box you will continue to be supplied and the solar system will work as well.

HEALTH STATUS MONITORING

Ensuring that the complete system is functioning efficiency at all times.

**Standard with 11 or 35 kW
Inverter, on-Board Transformer
and Switch Function**

Storage up to 120 kWh



Text and illustrations correspond to the technical state at the time of printing.
Subject to change.

All information is despite careful processing without guarantee - liability excluded.
© 2020 xelectrix Power GmbH. All rights reserved.

XPB-P		P-11	P-35
Unit Details	Dimensions (LxWxH)	2400 x 1200 x 1959-2400 mm	
	Base Weight	1000-2700 kg (depending on battery capacity)	
	Lifting Points	Forklift points and annular nuts for lifting with a crane	
	Protection	IP 68 (Battery Pack)	
Use	Application	Indoor & Outdoor	
	Mounting	Skid-Mounted / easily transportable	
	Max. Altitude	5000 m (with a derating above 3000 m)	
Power Electronics	Inverter Power	11 kW	35 kW
	Transformer	On-Board as Standard / 400 V, 3P+N+PE	
	Switch Function	On-Board as Standard	
Storage	Battery Type	Lithium Iron Phosphate (LiFePO ₄)	
	Cell Cup Class	32650 Screwed	
	Net. Capacity	20 kWh (Standard) expandable to 120 kWh (in 20 kWh modules)	40 kWh (Standard) expandable to 120 kWh (in 20 kWh modules)
	Nominal Battery Voltage	650 V DC	
	Management	aBMS (active Battery Management System)	
	Heating	Heating Controller and Wiring Standard (ready for Mats)	
Connection	AC-input	63 A CEE (up to 40 kVA diesel generator)	250 A max. (up to 175 kVA diesel generator)
	AC-Output	63 A max. per phase	300 A max. per phase
	Types of Network	IT / TN / TN-C / TN-S	
	Grid Frequency	EU: 50 Hz (45-55 Hz)	
	XPB Connection Interface	Input: 63A CEE Output: 1 x 32A CEE / 1 x 16A CEE / 3 x 16 A1P	Input: 125A CEE Output: 2 x 63A CEE / 1 x 32A CEE / 1 x 16A CEE, 3 x 16 A1P
Safety	Cell Operating Range	-20 to +60°C discharge +5 to +55°C charge	
	Protection Measures	integrated Thermal Management (passive cooling), integrated Voltage Protection, integrated Cell Internal Resistance Monitoring, integrated Over Current Protection (aBMS ≥ 75 A, Fuse 100 A)	
	Fire Protection	Thermally triggered extinguishing system (N ₂ / CO ₂) in every Battery Pack	
Options	Cold Climate Package Cabinet, Cold Climate Package Mats (per Battery Pack) Tropical Climate Package for Cooling 60 Hz (55-65 Hz) Version Customized Selection of AC Outlets / Removal of AC Outlet Connection and Replacement with a Hard Wired System Country specific Transformers 250 A Input Option As Trailer or Crawler Version (release date to be advised)		

DISCOVER NEW ENERGY

Hugo Tillquist
 Box 1120, 164 22 Kista
 Finlandsgatan 16, Kista, Sweden
 Tel +46 8 594 632 00
www.tillquist.com