

## Mått och Hålltagning BSM/USM-serien

### Mechanical Data

| Typ<br>BSM/USM        | Front frame<br>H x W x D [mm] | front panel [mm] | Depth with front frame<br>and terminals [mm] | Weight [kg]  |
|-----------------------|-------------------------------|------------------|----------------------------------------------|--------------|
| 08                    | 96 x 96 x 8                   | 92 x 92          | 100                                          | approx. 0,40 |
| 16                    | 96 x 96 x 8                   | 92 x 92          | 100                                          | approx. 0,45 |
| 16 Wide-housing<br>24 | 96 x 192 x 8                  | 92 x 186         | 100                                          | approx. 0,70 |
| 40<br>48              | 96 x 287 x 8                  | 92 x 282         | 100                                          | approx. 1,00 |

|                 |                |
|-----------------|----------------|
| <b>Mounting</b> | panel mounting |
|-----------------|----------------|

|                             |        |
|-----------------------------|--------|
| Required installation depth | 120 mm |
|-----------------------------|--------|

|                                             |       |
|---------------------------------------------|-------|
| Minimum horizontal gap<br>between 2 devices | 15 mm |
|---------------------------------------------|-------|

|                      |           |
|----------------------|-----------|
| Connection terminals | pluggable |
|----------------------|-----------|

|                                      |  |
|--------------------------------------|--|
| Wire cross section rigid or flexible |  |
|--------------------------------------|--|

|                      |                             |
|----------------------|-----------------------------|
| Without wire sleeves | 0,2 ... 2,5 mm <sup>2</sup> |
|----------------------|-----------------------------|

|                   |                              |
|-------------------|------------------------------|
| With wire sleeves | 0,25 ... 2,5 mm <sup>2</sup> |
|-------------------|------------------------------|